



- Work surface size (mm) 800 × 1700
- Left and right stroke (X) (mm) 1500
- Front and rear stroke (Y) (mm) 800
- Up / down stroke (Z) (mm) 700
- Spindle center-to-post rail distance (mm) 810
- Spindle face to countertop distance (mm) 130-830
- Table T-slot (number-size × spacing) 5-22×140
- Spindle taper BT50
- Spindle speed (r/min) 8000
- X, Y, Z-axis ball screw specifications 6310, 6310, 5010
- X, Y, Z fast moving speed (m/min) 20, 20, 15
- Z-axis guide rail
- X, Y, Z motor connection directly connected
- Main motor power (kw) 18.5
- X, Y, Z-axis motor torque (N.m) 24, 26, 26
- Table load (kg) 1500
- Light machine net weight approx (kg) 13000

Standard Accessories	Optional
1. Resin Sand Casting (X / Y Ball Line Rail. Z Axis Hard Rail)	1. Hats Type Magazine (Taiwan / Okada)
2. Ball Screw (Taiwan Silver / Intime)	2. Disc Type Magazine (Taiwan / Okada)
3. Spindle (Taiwan Pusen / Luo Yi / Dan Quan)	3. Chip Conveyor (Domestic)
4. Knife Cylinder (Taiwan Still Products)	4. Spindle Oil Cooler
5. Spindle Timing Belt Pulleys. Timing Belt (Taiwan)	5. The Fourth Axis (Taiwan)
6. Bearing (Only Industry Extra Japan, Nsk)	
7. X. Y. Z Axis Stainless Steel Protective Cover	
8. Mitsubishi M80 System	
9. Three-Axis Mitsubishi Servo Motor	
10. The Host Of Electrical Appliances (Germany Schneider)	
11. Processing Blowing Device (Taiwan Yade Off)	
12. Processing Flushing Device (Taiwan Zhangtie)	
13. Electric Lubrication System (China-Japan Joint Venture)	
14. Fully Enclosed Housing	
15. Electric Heat Exchanger (Ea-05N)	
16. Adjust The Horn+Screws. Tools. File Box	
17. Led Long-Life Work Lamp 1	