



Standard accessories:	Optional:
1. Resin sand casting (X/Y axis rail. Z-axis hard rail)	1. Disc type tool magazine (Taiwan)
2. ball screw. wire rail (Taiwan Shangyin / Yintai)	2. Fighting knife magazine (Taiwan)
3. BT40 spindle 8000 rpm (Taiwan Pusen / Luo Yi / Tanjung)	3. Spindle oil cooling (WHO)
4. Knife cylinder (Taiwan still goods)	4. Chip conveyor
5. Spindle synchronous pulley timing belt (Taiwan)	5. The fourth axis (Taiwan Tanjia)
6. Bearings (Only InDustry EXTRA Japan or NSK)	
7. X. Y. Z axis stainless steel protective cover	
8. Japan's Mitsubishi M80 system	
9. Three-axis Mitsubishi original servo motor	
10. Host electrical appliances (Schneider. Germany)	
11. Processing air blowing device (Taiwan Ya Deke)	
12. Processing oil flushing device (Taiwan Zhangtie)	
13. Electric lubrication system (Sino-Japanese joint venture valley)	
14. Fully enclosed cover	
15. Electric box heat exchanger (EA-05N)	
16. Adjust the horn + screws. tools. file boxes	
17. LED long life work light 1	

Moving trip

- X axis (table left and right stroke) stroke: 800 mm
- Y axis (table front and rear stroke) stroke: 500 mm
- Z axis (spindle head up and down stroke) stroke: 530 mm
- Spindle center to column guide distance: 550 mm
- Main shaft nose to work station Distance: 126-656mm

Specifications

- Workbench size: 500×1050mm
- T-slot number: 5
- T-slot width: 18mm
- Worktable maximum load: 600kg
- Spindle speed series: inorganic speed regulation
- Spindle speed range: 60~8000rpm
- Main shaft Cone hole: BT40-Ø150